



Message Implementation Guideline

DSV_InvoiceMessage

Model: DSV XML Invoice outbound
Version: v1.5
Issue date: 2022-03-28
Author: DSV A/S, EDI

2 Change Log	2
3 Structure.....	4
4 Guideline	13



Change Log

No	Changes
01	<p>Date (YYYY-MM-DD) 2021-05-06 Author DSV Panalpina A/S, EDI CRQ v1.2</p> <p>Tag Taxes Path DSV_InvoiceMessage/Invoice/Taxes Change Description MonetaryAmounts with CurrencyType= "InvoicingCurrency" will be grouped under TaxType= "Tax". MonetaryAmounts with CurrencyType= "HomeCurrency" will be grouped under TaxType= "TaxRelatedInformation".</p>
02	<p>Date (YYYY-MM-DD) 2021-08-17 Author DSV Panalpina A/S, EDI CRQ v1.3</p> <p>Tag Type Path DSV_InvoiceMessage/Invoice/References/ReferenceGroup/Reference/@Type Change Description Added "AirWayBill" to applicable Codes.</p>
03	<p>Date (YYYY-MM-DD) 2021-08-17 Author DSV Panalpina A/S, EDI CRQ v1.3</p> <p>Tag Type Path DSV_InvoiceMessage/Invoice/InvoiceLines/InvoiceLine/References/ReferenceGroup/Reference/@Type Change Description Added "AirWayBill" to applicable Codes.</p>
04	<p>Date (YYYY-MM-DD) 2021-08-17 Author DSV Panalpina A/S, EDI CRQ v1.3</p> <p>Tag Type Path DSV_InvoiceMessage/Invoice/MonetaryAmounts/MonetaryAmount/@Type Change Description Added "TotalAmount" to applicable Codes.</p>
05	<p>Date (YYYY-MM-DD) 2021-09-28 Author DSV A/S, EDI CRQ ver 1.4</p> <p>Tag FinancialInstitution Path DSV_InvoiceMessage/Invoice/Parties/Party/FinancialInstitution Change Description Updated description for AccountHolderId, AccountHolderName, InstitutionCode, InstitutionBranchId, InstitutionName and enabled InstitutionBranchLocationName</p>
06	<p>Date (YYYY-MM-DD) 2021-09-28 Author DSV A/S, EDI CRQ ver 1.4</p> <p>Tag InstitutionBranchLocationName Path DSV_InvoiceMessage/Invoice/Parties/Party/FinancialInstitution/InstitutionBranchLocationName Change Description Enabled "InstitutionBranchLocationName" for BankName</p>
07	<p>Date (YYYY-MM-DD) 2022-01-25 Author DSV A/S, EDI CRQ v1.5</p> <p>Tag Rate Path DSV_InvoiceMessage/Invoice/InvoiceLines/InvoiceLine/AllowancesorCharges/AllowanceOrChargeGroup/Rate</p>



Change Log

No	Changes		
	<table><tr><td>Change Description</td><td>Enabled Rate for "SystemExchangeRate" to be mapped from RTE SG44, which will be repeated for each AllowanceOrChargeGroup.</td></tr></table>	Change Description	Enabled Rate for "SystemExchangeRate" to be mapped from RTE SG44, which will be repeated for each AllowanceOrChargeGroup.
Change Description	Enabled Rate for "SystemExchangeRate" to be mapped from RTE SG44, which will be repeated for each AllowanceOrChargeGroup.		

Structure

Occurrence	Element/Attribute
	DSV_InvoiceMessage
1 .. 1	xs:sequence
1 .. 1	Header
1 .. 1	xs:sequence
1 .. 1	MessageId
1 .. 1	SenderId
1 .. 1	ReceiverId
1 .. 1	DocumentDate
required	<i>Type</i>
required	<i>Format</i>
1 .. 1	xs:sequence
0 .. 1	DateTime
1 .. 1	DocumentCode
1 .. 1	Function
1 .. 1	Version
1 .. 1	Invoice
1 .. 1	xs:sequence
1 .. 1	InvoiceId
0 .. 1	Dates
1 .. 1	xs:sequence
0 .. unbounded	Date
required	<i>Type</i>
required	<i>Format</i>
1 .. 1	xs:sequence
0 .. 1	DateTime
0 .. 1	FreeTextData
1 .. 1	xs:sequence
0 .. unbounded	FreeText
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	TextLine1
0 .. 1	TextLine2
0 .. 1	TextLine3
0 .. 1	TextLine4
0 .. 1	TextLine5
0 .. 1	Locations
1 .. 1	xs:sequence
0 .. unbounded	LocationGroup
1 .. 1	xs:sequence
0 .. 1	Location
required	<i>Type</i>
1 .. 1	xs:sequence
1 .. unbounded	LocationIdentification
1 .. 1	xs:sequence
0 .. 1	LocationIdentifier
0 .. 1	LocationName
0 .. 1	References
1 .. 1	xs:sequence

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
0 .. unbounded	ReferenceGroup
1 .. 1	xs:sequence
0 .. 1	Reference
required	Type
0 .. 1	Parties
1 .. 1	xs:sequence
0 .. unbounded	Party
1 .. 1	xs:sequence
0 .. 1	PartyDetails
required	Role
1 .. 1	xs:sequence
0 .. 1	Id
0 .. 1	Assignor
0 .. 1	PartyName
0 .. 1	AddressLine1
0 .. 1	AddressLine2
0 .. 1	AddressLine3
0 .. 1	CityName
0 .. 1	State
0 .. 1	PostCode
0 .. 1	CountryCode
0 .. unbounded	FinancialInstitution
required	Role
1 .. 1	xs:sequence
0 .. 1	AccountHolderId
0 .. 1	AccountHolderName
0 .. 1	InstitutionNameCode
0 .. 1	ResponsibleAgencyCode
0 .. 1	InstitutionBranchId
0 .. 1	InstitutionName
0 .. 1	InstitutionBranchLocationName
0 .. 1	References
1 .. 1	xs:sequence
0 .. unbounded	ReferenceGroup
1 .. 1	xs:sequence
0 .. 1	Reference
required	Type
0 .. 1	Documents
1 .. 1	xs:sequence
0 .. unbounded	Document
1 .. 1	xs:sequence
0 .. 1	DocumentCode
0 .. unbounded	Contact
required	Type
1 .. 1	xs:sequence
0 .. 1	Name
0 .. 1	Phone
0 .. 1	Email
0 .. 1	Currencies
1 .. 1	xs:sequence

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
0 .. unbounded	CurrencyDetails
1 .. 1	xs:sequence
0 .. 1	Currency
1 .. 1	xs:sequence
0 .. 1	CurrencyUsage
0 .. 1	CurrencyIdentification
0 .. 1	CurrencyCode
0 .. 1	CurrencyRate
0 .. 1	Dates
1 .. 1	xs:sequence
0 .. unbounded	Date
required	Type
required	Format
1 .. 1	xs:sequence
0 .. 1	DateTime
0 .. 1	PaymentTerms
1 .. 1	xs:sequence
0 .. unbounded	PaymentTermsDetails
1 .. 1	xs:sequence
1 .. 1	PaymentTerms
required	Type
1 .. 1	xs:sequence
0 .. 1	PaymentTermsDescription
0 .. 1	PeriodType
0 .. 1	PeriodCount
0 .. 1	Dates
1 .. 1	xs:sequence
0 .. unbounded	Date
required	Type
required	Format
1 .. 1	xs:sequence
0 .. 1	DateTime
0 .. 1	TransportStages
1 .. 1	xs:sequence
0 .. unbounded	TransportStage
1 .. 1	xs:sequence
0 .. 1	Stage
required	Type
1 .. 1	xs:sequence
0 .. 1	ModeOfTransport
0 .. 1	TransportId
0 .. 1	CarrierId
0 .. 1	CarrierName
0 .. 1	TransportType
0 .. 1	TransportMeansName
0 .. 1	TransportServices
1 .. 1	xs:sequence
0 .. unbounded	TransportService
1 .. 1	xs:sequence
0 .. 1	ServiceCode

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
0 .. 1	PriorityCode
0 .. 1	Locations
1 .. 1	xs:sequence
0 .. unbounded	LocationGroup
1 .. 1	xs:sequence
0 .. 1	Location
required	Type
1 .. 1	xs:sequence
1 .. unbounded	LocationIdentification
1 .. 1	Type
0 .. 1	xs:sequence
0 .. 1	LocationIdentifier
0 .. 1	LocationName
0 .. 1	Dates
1 .. 1	xs:sequence
0 .. unbounded	Date
required	Type
required	Format
1 .. 1	xs:sequence
0 .. 1	DateTime
0 .. 1	References
1 .. 1	xs:sequence
0 .. unbounded	ReferenceGroup
1 .. 1	xs:sequence
0 .. 1	Reference
required	Type
0 .. 1	TermsOfDelivery
1 .. 1	xs:sequence
0 .. 1	Terms
1 .. 1	xs:sequence
0 .. 1	TermCode
0 .. 1	CodeId
0 .. unbounded	Location
required	Type
1 .. 1	xs:sequence
1 .. unbounded	LocationIdentification
1 .. 1	xs:sequence
0 .. 1	LocationName
0 .. 1	EquipmentUnits
1 .. 1	xs:sequence
0 .. unbounded	EquipmentUnit
1 .. 1	xs:sequence
0 .. 1	EquipmentType
1 .. 1	xs:sequence
0 .. 1	Type
0 .. 1	UnitId
0 .. 1	SizeTypeCode
0 .. 1	PackingMode
0 .. 1	SealIds

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
1 .. 1	xs:sequence
0 .. unbounded	Seal
1 .. 1	xs:sequence
0 .. 1	SealId
0 .. 1	InvoiceLines
1 .. 1	xs:sequence
0 .. unbounded	InvoiceLine
1 .. 1	xs:sequence
0 .. 1	LinItem
1 .. 1	xs:sequence
0 .. 1	LinItemNumber
0 .. 1	ItemIdentifier
0 .. 1	ItemDescriptions
1 .. 1	xs:sequence
0 .. unbounded	ItemDescription
required	<i>DescriptionFormatCode</i>
1 .. 1	xs:sequence
0 .. 1	ItemCharacteristicCode
0 .. 1	ItemDescription
0 .. 1	Measurements
1 .. 1	xs:sequence
0 .. unbounded	Measurement
required	<i>Type</i>
	<i>Uom</i>
1 .. 1	xs:sequence
0 .. 1	Measure
0 .. 1	Dates
1 .. 1	xs:sequence
0 .. unbounded	Date
required	<i>Type</i>
required	<i>Format</i>
1 .. 1	xs:sequence
0 .. 1	DateTime
0 .. 1	EquipmentUnits
1 .. 1	xs:sequence
0 .. unbounded	EquipmentUnit
1 .. 1	xs:sequence
0 .. 1	EquipmentType
1 .. 1	xs:sequence
0 .. 1	Type
0 .. 1	UnitId
0 .. 1	SizeTypeCode
0 .. 1	ISOCODE
0 .. 1	PackingMode
0 .. 1	FreeTextData
1 .. 1	xs:sequence
0 .. unbounded	FreeText
required	<i>Type</i>
1 .. 1	xs:sequence

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
0 .. 1	TextLine1
0 .. 1	TextLine2
0 .. 1	MonetaryAmounts
1 .. 1	xs:sequence
0 .. unbounded	MonetaryAmount
required	Type
1 .. 1	xs:sequence
0 .. 1	Amount
0 .. 1	Currency
0 .. 1	CurrencyType
0 .. 1	References
1 .. 1	xs:sequence
0 .. unbounded	ReferenceGroup
1 .. 1	xs:sequence
0 .. 1	Reference
required	Type
0 .. 1	Packages
1 .. 1	xs:sequence
0 .. unbounded	PackageGroup
1 .. 1	xs:sequence
0 .. 1	Package
1 .. 1	xs:sequence
1 .. 1	PackageQuantity
0 .. 1	PackageCode
0 .. 1	Packageld
1 .. 1	xs:sequence
1 .. 1	InstructionCode
0 .. 1	Marks
1 .. 1	xs:sequence
1 .. unbounded	ShippingMark
0 .. 1	Locations
1 .. 1	xs:sequence
0 .. unbounded	LocationGroup
1 .. 1	xs:sequence
0 .. 1	Location
required	Type
1 .. 1	xs:sequence
1 .. unbounded	LocationIdentification
	Type
1 .. 1	xs:sequence
0 .. 1	LocationIdentifier
0 .. 1	LocationName
0 .. 1	Taxes
1 .. 1	xs:sequence
0 .. unbounded	TaxDetails
1 .. 1	xs:sequence
0 .. 1	Tax
required	Type
1 .. 1	xs:sequence

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
0 .. 1	TaxRate
0 .. 1	TaxCode
0 .. 1	TaxCategory
0 .. 1	MonetaryAmounts
1 .. 1	xs:sequence
0 .. unbounded required	MonetaryAmount
1 .. 1	Type
0 .. 1	xs:sequence
0 .. 1	Amount
0 .. 1	Currency
0 .. 1	CurrencyType
0 .. 1	Parties
1 .. 1	xs:sequence
0 .. unbounded	Party
1 .. 1	xs:sequence
0 .. 1 required	PartyDetails
1 .. 1	Role
0 .. 1	xs:sequence
0 .. 1	Id
0 .. 1	PartyName
0 .. 1	AddressLine1
0 .. 1	AddressLine2
0 .. 1	AddressLine3
0 .. 1	CityName
0 .. 1	State
0 .. 1	PostCode
0 .. 1	CountryCode
0 .. 1	AllowancesorCharges
1 .. 1	xs:sequence
0 .. unbounded	AllowanceOrChargeGroup
1 .. 1	xs:sequence
0 .. 1 required	AllowanceOrCharge
1 .. 1	AllowanceOrChargeCode
0 .. 1	xs:sequence
0 .. 1	AllowanceOrChargeIdentifier
0 .. 1	SpecialServiceDescriptionCode
0 .. 1	SpecialServiceDescription
0 .. 1	MonetaryAmounts
1 .. 1	xs:sequence
0 .. unbounded	MonetaryAmountGroup
1 .. 1	xs:sequence
0 .. 1 required	MonetaryAmount
1 .. 1	Type
0 .. 1	xs:sequence
0 .. 1	Amount
0 .. 1	Currency
0 .. 1	CurrencyType
0 .. 1	Currencies
1 .. 1	xs:sequence
0 .. unbounded	CurrencyDetails

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group

Occurrence	Element/Attribute
1 .. 1	xs:sequence
0 .. 1	Currency
1 .. 1	xs:sequence
0 .. 1	CurrencyUsage
0 .. 1	CurrencyIdentification
0 .. 1	CurrencyCode
0 .. 1	CurrencyRate
0 .. 1	Taxes
1 .. 1	xs:sequence
0 .. unbounded	TaxDetails
1 .. 1	xs:sequence
0 .. 1	Tax
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	TaxRate
0 .. 1	TaxCode
0 .. 1	TaxCategory
0 .. 1	MonetaryAmounts
1 .. 1	xs:sequence
0 .. unbounded	MonetaryAmount
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	Amount
0 .. 1	Currency
0 .. 1	CurrencyType
0 .. 1	Rate
optional	<i>Type</i>
0 .. 1	TransportStages
1 .. 1	xs:sequence
0 .. unbounded	TransportStage
1 .. 1	xs:sequence
0 .. 1	Stage
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	ModeOfTransport
0 .. 1	CarrierId
0 .. 1	CarrierName
0 .. 1	TransportMeansName
0 .. 1	Locations
1 .. 1	xs:sequence
0 .. unbounded	LocationGroup
1 .. 1	xs:sequence
0 .. 1	Location
required	<i>Type</i>
1 .. 1	xs:sequence
1 .. unbounded	LocationIdentification
	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	LocationIdentifier
0 .. 1	LocationName

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Occurrence	Element/Attribute
0 .. 1	TermsOfDelivery
1 .. 1	xs:sequence
0 .. 1	Terms
1 .. 1	xs:sequence
0 .. 1	TermCode
0 .. 1	CodeId
0 .. unbounded	Location
required	<i>Type</i>
1 .. 1	xs:sequence
1 .. unbounded	LocationIdentification
1 .. 1	xs:sequence
0 .. 1	LocationName
0 .. 1	MonetaryAmounts
1 .. 1	xs:sequence
0 .. unbounded	MonetaryAmount
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	Amount
0 .. 1	Currency
0 .. 1	CurrencyType
0 .. 1	Taxes
1 .. 1	xs:sequence
0 .. unbounded	TaxDetails
1 .. 1	xs:sequence
0 .. 1	Tax
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	TaxRate
0 .. 1	TaxCode
0 .. 1	TaxCategory
0 .. 1	MonetaryAmounts
1 .. 1	xs:sequence
0 .. unbounded	MonetaryAmount
required	<i>Type</i>
1 .. 1	xs:sequence
0 .. 1	Amount
0 .. 1	Currency
0 .. 1	CurrencyType

Bold = Simple Element, Bold on grey background = Complex Element, Italic = Attribute, Grey = Group



Guideline

Element/Attribute	Annotation
DSV_InvoiceMessage	Type <i>dsv_invoicemessage:DSV_InvoiceMessage</i>
xs:sequence	Occurrence 1 .. 1
Header	Occurrence 1 .. 1 Type <i>sharedelements:Header</i> General Notes MESSAGE HEADER Examples <Header> <MessageId>12485236</MessageId> <SenderId>SenderIdentification</SenderId> <ReceiverId>ReceiverIdentification</ReceiverId> <DocumentDate Type="IssueDate" Format="DateTime"> <DateTime>202002120000</DateTime> </DocumentDate> <DocumentCode>Invoice</DocumentCode> <Function>New</Function> <Version>1.0</Version> </Header>
xs:sequence	Occurrence 1 .. 1
MessageId	Occurrence 1 .. 1 Type <i>xs:string</i> General Notes MESSAGE IDENTIFIER
SenderId	Occurrence 1 .. 1 Type <i>xs:string</i> General Notes SENDER IDENTIFICATION Mutually agreed
ReceiverId	Occurrence 1 .. 1 Type <i>xs:string</i> General Notes RECEIVER IDENTIFICATION Mutually agreed
DocumentDate	Occurrence 1 .. 1 Type <i>sharedelements:Date</i> General Notes DOCUMENT / MESSAGE DATE
Type	Type <i>xs:string</i> Use required General Notes DATE TYPE Applicable Codes IssueDate Document Issued Date
Format	Type <i>xs:string</i> Use required General Notes DATE FORMAT Applicable Codes DateTime CCYYMMDDHHMM
xs:sequence	Occurrence 1 .. 1
DateTime	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes MESSAGE / DOCUMENT DATE
DocumentCode	Occurrence 1 .. 1 Type <i>xs:string</i> General Notes DOCUMENT CODE Applicable Codes CommercialInvoice Commercial Invoice

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	Applicable Codes
	CreditNote CreditNote
Function	Occurrence 1 .. 1
	Type xs:string
	General Notes MESSAGE FUNCTION
	Applicable Codes
	Delete Delete
	New New
	Update Update
Version	Occurrence 1 .. 1
	Type xs:string
	General Notes MESSAGE VERSION
	Applicable Codes
	1.0 Version 1.0
Invoice	Occurrence 1 .. 1
	Type invoice:Invoice
xs:sequence	Occurrence 1 .. 1
InvoiceId	Occurrence 1 .. 1
	Type xs:string
	General Notes INVOICE IDENTIFIER
	Examples
	<InvoiceId>INVOICE123</InvoiceId>
Dates	Occurrence 0 .. 1
	Type invoice:DateList
	General Notes INVOICE DATES
	Examples
	<Dates>
	<Date Type="InvoiceDate" Format="DateTime">
	<DateTime>202002130900</DateTime>
	</Date>
	<Date Type="IssueDate" Format="DateTime">
	<DateTime>202002130900</DateTime>
	</Date>
	</Dates>
xs:sequence	Occurrence 1 .. 1
Date	Occurrence 0 .. unbounded
	Type sharedelements:Date
	General Notes INVOICE DATE
Type	Type xs:string
	Use required
	General Notes DATE TYPE
	Applicable Codes
	InvoiceIssue Invoice Issue Date
	IssueDate Document Issued Date
Format	Type xs:string
	Use required
	General Notes DATE FORMAT
	Applicable Codes
	DateTime YYYYMMDDHHMM
xs:sequence	Occurrence 1 .. 1
DateTime	Occurrence 0 .. 1
	Type xs:string
	General Notes DATE / TIME

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation				
FreeTextData	<p>Occurrence 0 .. 1 Type <i>invoice:FreeTextList</i> General Notes INVOICE FREE TEXT</p> <p>Examples</p> <pre> <FreeTextData> <FreeText Type="Note"> <TextLine1>Notes Text Line 1</TextLine1> <TextLine2>Notes Text Line 2</TextLine2> <TextLine3>Notes Text Line 3</TextLine3> <TextLine4>Notes Text Line 4</TextLine4> <TextLine5>Notes Text Line 5</TextLine5> </FreeText> </FreeTextData> <FreeTextData> <FreeText Type="DocumentIssuerDeclaration" > <TextLine1>EAN:991122333</TextLine1> </FreeText> </FreeTextData> </pre>				
xs:sequence	<p>Occurrence 1 .. 1</p>				
FreeText	<p>Occurrence 0 .. unbounded Type <i>sharedElements:FreeText</i> Type <i>xs:string</i> Use required General Notes FREE TEXT TYPE</p> <p>Applicable Codes</p> <table> <tr> <td>DocumentIssuerDeclaration</td><td>Document Issuer Declaration</td></tr> <tr> <td>Note</td><td>Note</td></tr> </table>	DocumentIssuerDeclaration	Document Issuer Declaration	Note	Note
DocumentIssuerDeclaration	Document Issuer Declaration				
Note	Note				
xs:sequence	<p>Occurrence 1 .. 1</p>				
TextLine1	<p>Occurrence 0 .. 1 Type <i>xs:string</i> General Notes FREE TEXT LINE 1</p>				
TextLine2	<p>Occurrence 0 .. 1 Type <i>xs:string</i> General Notes FREE TEXT LINE 2</p>				
TextLine3	<p>Occurrence 0 .. 1 Type <i>xs:string</i> General Notes FREE TEXT LINE 3</p>				
TextLine4	<p>Occurrence 0 .. 1 Type <i>xs:string</i> General Notes FREE TEXT LINE 4</p>				
TextLine5	<p>Occurrence 0 .. 1 Type <i>xs:string</i> General Notes FREE TEXT LINE 5</p>				
Locations	<p>Occurrence 0 .. 1 Type <i>invoice:LocationGroupList</i> General Notes INVOICE LOCATIONS</p> <p>Examples</p> <pre> <Locations> <LocationGroup> <Location Type="PlaceOfBusiness" > <LocationIdentification> <LocationIdentifier>I200</LocationIdentifier> <LocationName>GOT_FIS</LocationName> </LocationIdentification> </Location> </LocationGroup> </Locations> </pre>				

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
Examples </LocationIdentification> </Location> </LocationGroup> </Locations>	
xs:sequence	Occurrence 1 .. 1
LocationGroup	Occurrence 0 .. unbounded
	Type <i>invoice:LocationGroup</i>
xs:sequence	Occurrence 1 .. 1
Location	Occurrence 0 .. 1
	Type <i>sharedelements:Location</i>
Type	Type <i>xs:string</i>
	Use required
	General Notes LOCATION TYPE
Applicable Codes PlaceOfBusiness Place Of Business	
xs:sequence	Occurrence 1 .. 1
LocationIdentification	Occurrence 1 .. unbounded
	Type <i>sharedelements:LocationIdentification</i>
xs:sequence	Occurrence 1 .. 1
LocationIdentifier	Occurrence 0 .. 1
	Type <i>xs:string</i>
	General Notes LOCATION IDENTIFIER
LocationName	Occurrence 0 .. 1
	Type <i>xs:string</i>
	General Notes LOCATION Name
References	Occurrence 0 .. 1
	Type <i>invoice:ReferenceGroupList</i>
	General Notes INVOICE REFERENCES
Examples <References> <ReferenceGroup> <Reference Type="ShipmentReference">SKUL1234567</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="HouseBill">111-12345678</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="MasterBill">111-89012345</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="ShipperReference">S42900531</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="ConsigneeReference">ConsRef1</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="OrderReference">SI1HA1123456</Reference> </ReferenceGroup> </References>	
xs:sequence	Occurrence 1 .. 1
ReferenceGroup	Occurrence 0 .. unbounded
	Type <i>invoice:ReferenceGroup</i>
xs:sequence	Occurrence 1 .. 1

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
Reference	Occurrence 0 .. 1 Type <i>sharedelements:Reference</i> General Notes INVOICE REFERENCE
Type	Type xs:string Use required General Notes REFERENCE TYPE <i>Predefined Types listed, additional reference types to be agreed</i>
Applicable Codes	
AirWayBill	Air waybill number
CargoManifestNo	Cargo manifest number, Transport Id
ConsigneeReference	Consignee Reference
ExchangeRate	Exchange Rate
GINCNumber	Waybill number, GINC
HouseBill	House bill of lading number
LanguageCode	Language Code
MasterBill	Master Bill
OrderReference	Order Reference
OriginatorsReference	Originator's Reference
PaymentId	Payment Id
PaymentReference	Payment Reference
RoadWaybill	Road Waybill number, SIS
ShipmentReference	Shipment reference number
ShipperReference	Shipper Reference
TaxCategory	Tax and Category
TransactionsCount	Transactions Count
TransportInstructionNumber	Transport instruction number
USDToEUROExchangeRate	USD To EUR Exchange Rate
Parties	Occurrence 0 .. 1 Type <i>invoice:PartiesList</i> General Notes INVOICE PARTIES
xs:sequence	Occurrence 1 .. 1
Party	Occurrence 0 .. unbounded Type <i>invoice:Party</i>
xs:sequence	Occurrence 1 .. 1
PartyDetails	Occurrence 0 .. 1 Type <i>sharedelements:PartyDetails</i> General Notes INVOICE PARTY DETAILS
Examples	
<pre> <PartyDetails Role="InvoiceIssuer"> <Id>InvoiceIssuerID</Id> <Assignor>InvoiceIssuer</Assignor> <PartyName>InvoiceIssuer Name</PartyName> <AddressLine1>InvoiceIssuer Addr Line 1</AddressLine1> <AddressLine2>InvoiceIssuer Addr Line 2</AddressLine2> <AddressLine3>InvoiceIssuer Addr Line 3</AddressLine3> <CityName>InvoiceIssuer City</CityName> <State>InvoiceIssuer State</State> <PostCode>PostCd</PostCode> <CountryCode>DK</CountryCode> </PartyDetails> </pre>	
Role	Type xs:string Use required General Notes INVOICE PARTY ROLE
Applicable Codes	
InvoiceIssuer	Invoice issuer

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
Applicable Codes	
Invoice	Invoicee
xs:sequence	Occurrence 1 .. 1
Id	Occurrence 0 .. 1
	Type xs:string
General Notes	PARTY IDENTIFIER
Assignor	Occurrence 0 .. 1
	Type xs:string
General Notes	PARTY IDENTIFIER ASSIGNOR
Applicable Codes	
Consignor	Consignor
DSV	DSV
GS1	GS1
PartyName	Occurrence 0 .. 1
	Type xs:string
General Notes	PARTY NAME
AddressLine1	Occurrence 0 .. 1
	Type xs:string
General Notes	PARTY ADDRESS LINE 1
AddressLine2	Occurrence 0 .. 1
	Type xs:string
General Notes	PARTY ADDRESS LINE 2
AddressLine3	Occurrence 0 .. 1
	Type xs:string
General Notes	PARTY ADDRESS LINE 3
CityName	Occurrence 0 .. 1
	Type xs:string
General Notes	PARTY CITY NAME
State	Occurrence 0 .. 1
	Type xs:string
General Notes	PARTY STATE OR PROVINCE
PostCode	Occurrence 0 .. 1
	Type xs:string
General Notes	PARTY POST OR ZIP CODE
CountryCode	Occurrence 0 .. 1
	Type xs:string
General Notes	PARTY LOCATION ISO COUNTRY CODE
FinancialInstitution	Occurrence 0 .. unbounded
	Type sharedElements:FinancialInstitution
General Notes	PARTY FINANCIAL INSTITUTION DETAILS
Examples	
<FinancialInstitution Role="InvoiceIssuer" > <AccountHolderId>1211 AVENUE OF THE AMERICAS, 23RD FLOOR, NEW YORK, NY 10036</AccountHolderId> <AccountHolderName>DSV AIR & SEA INC.</AccountHolderName> <InstitutionNameCode>NDEAUS3N</InstitutionNameCode> <ResponsibleAgencyCode>SWIFT</ResponsibleAgencyCode> <InstitutionBranchId>7169853001</InstitutionBranchId> <InstitutionName>026010786</InstitutionName> </FinancialInstitution>	
Role	Type xs:string
Use	required

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	General Notes <i>FINANCIAL INSTITUTION ROLE</i>
	Applicable Codes
	InvoiceIssuer <i>Invoice issuer</i>
xs:sequence	Occurrence 1 .. 1
AccountHolderId	Occurrence 0 .. 1
	Type <i>xs:string</i>
	General Notes <i>ACCOUNT HOLDER IDENTIFIER</i> <i>IBAN nr/BankAddress</i>
AccountHolderName	Occurrence 0 .. 1
	Type <i>xs:string</i>
	General Notes <i>ACCOUNT HOLDER NAME</i>
InstitutionNameCode	Occurrence 0 .. 1
	Type <i>xs:string</i>
	General Notes <i>INSTITUTION NAME CODE</i> <i>SWIFT code</i>
ResponsibleAgencyCode	Occurrence 0 .. 1
	Type <i>xs:string</i>
	General Notes <i>RESPONSIBLE AGENCY CODE</i>
	Applicable Codes
	SWIFT <i>SWIFT</i>
InstitutionBranchId	Occurrence 0 .. 1
	Type <i>xs:string</i>
	General Notes <i>INSTITUTION BRANCH IDENTIFIER</i> <i>BankAccount number</i>
InstitutionName	Occurrence 0 .. 1
	Type <i>xs:string</i>
	General Notes <i>INSTITUTION NAME</i> <i>BranchNumber of Name of Bank</i>
InstitutionBranchLocationName	Occurrence 0 .. 1
	Type <i>xs:string</i>
References	Occurrence 0 .. 1
	Type <i>invoice:ReferenceGroupList</i>
	General Notes <i>PARTY REFERENCES</i>
	Examples
	<i><References></i>
	<i><ReferenceGroup></i>
	<i><Reference Type="VAT Registration number">VAT Registration number</Reference></i>
	<i></ReferenceGroup></i>
	<i></References></i>
xs:sequence	Occurrence 1 .. 1
ReferenceGroup	Occurrence 0 .. unbounded
	Type <i>invoice:ReferenceGroup</i>
xs:sequence	Occurrence 1 .. 1
Reference	Occurrence 0 .. 1
	Type <i>sharedElements:Reference</i>
	General Notes <i>REFERENCE</i>
Type	Type <i>xs:string</i>
	Use <i>required</i>
	General Notes <i>REFERENCE TYPE</i>
	<i>Predefined Types listed, additional reference types to be agreed</i>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	Applicable Codes VATRegistrationNumber VAT Registration number Occurrence 0 .. 1 Type <i>invoice:DocumentList</i> General Notes PARTY DOCUMENT DETAILS
Documents	Examples <Documents> <Document> <DocumentCode>ConsignmentInvoice</DocumentCode> </Document> </Documents>
xs:sequence	Occurrence 1 .. 1
Document	Occurrence 0 .. unbounded Type <i>sharedelements:Document</i>
xs:sequence	Occurrence 1 .. 1
DocumentCode	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes DOCUMENT TYPE
	Applicable Codes ConsignmentInvoice Consignment invoice ConsolidatedInvoice Consolidated invoice Occurrence 0 .. unbounded Type <i>sharedelements:Contact</i> General Notes PARTY CONTACT DETAILS
Contact	Examples <Contact Type="AccountsReceivableContact" > <Name>AccountReceivableContact</Name> <Phone>+123-45678901</Phone> <Email>contact@email.com</Email> </Contact>
Type	Type <i>xs:string</i> Use required General Notes PARTY CONTACT TYPE
	Applicable Codes AccountsPayableContact Accounts Payable Contact AccountsReceivableContact Accounts Receivable Contact Occurrence 1 .. 1
xs:sequence	Occurrence 0 .. 1
Name	Type <i>xs:string</i> General Notes PARTY CONTACT NAME
Phone	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes PARTY CONTACT TELEPHONE NUMBER
Email	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes PARTY CONTACT E-MAIL ADDRESS
Currencies	Occurrence 0 .. 1 Type <i>invoice:CurrencyGroupList</i> General Notes INVOICE CURRENCIES
	Examples <Currencies> <CurrencyDetails>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
Examples <pre> <Currency> <CurrencyUsage>ReferenceCurrency</CurrencyUsage> <CurrencyIdentification>MYR</CurrencyIdentification> <CurrencyCode>PricingCurrency</CurrencyCode> </Currency> <Dates> <Date Type="RateOfExchange" Format="Date" > <DateTime>20200210</DateTime> </Date> </Dates> </CurrencyDetails> </Currencies> </pre>	
xs:sequence	Occurrence 1 .. 1
CurrencyDetails	Occurrence 0 .. unbounded
	Type <i>invoice:CurrencyGroup</i>
xs:sequence	Occurrence 1 .. 1
Currency	Occurrence 0 .. 1
	Type <i>sharedelements:Currency</i>
xs:sequence	Occurrence 1 .. 1
CurrencyUsage	Occurrence 0 .. 1
	Type <i>xs:string</i>
	General Notes CURRENCY USAGE
Applicable Codes	
InvoicingCurrency	Invoicing Currency
ReferenceCurrency	Reference Currency
TargetCurrency	Target currency
CurrencyIdentification	Occurrence 0 .. 1
	Type <i>xs:string</i>
	General Notes CURRENCY IDENTIFICATION
CurrencyCode	Occurrence 0 .. 1
	Type <i>xs:string</i>
	General Notes CURRENCY CODE
Applicable Codes	
HomeCurrency	Home Currency
InvoicingCurrency	Invoicing Currency
PaymentCurrency	Payment Currency
PricingCurrency	Pricing Currency
CurrencyRate	Occurrence 0 .. 1
	Type <i>xs:string</i>
	General Notes CURRENCY RATE
Dates	Occurrence 0 .. 1
	Type <i>invoice:DateList</i>
xs:sequence	Occurrence 1 .. 1
Date	Occurrence 0 .. unbounded
	Type <i>sharedelements:Date</i>
	General Notes INVOICE CURRENCY DATE
Type	Type <i>xs:string</i>
	Use required
	General Notes DATE TYPE
Applicable Codes	
RateOfExchange	Rate of exchange date/time
Format	Type <i>xs:string</i>
	Use required

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
General Notes	DATE FORMAT
Applicable Codes	
Date	YYYYMMDD
Occurrence	1 .. 1
Occurrence	0 .. 1
Type	xs:string
General Notes	DATE / TIME
PaymentTerms	
Occurrence	0 .. 1
Type	invoice:PaymentTermsList
General Notes	INVOICE PAYMENT TERMS
Examples	
	<pre> <PaymentTerms> <PaymentTermsDetails> <PaymentTerms Type="FixedDate" > <PaymentTermsDescription>INV</PaymentTermsDescription> <PeriodType>Day</PeriodType> <PeriodCount>45</PeriodCount> </PaymentTerms> <Dates> <Date Type="TermsNetDue" Format="Date" > <DateTime>20200111</DateTime> </Date> </Dates> </PaymentTermsDetails> </PaymentTerms> </pre>
Occurrence	1 .. 1
Occurrence	0 .. unbounded
Type	invoice:PaymentTermsDetails
Occurrence	1 .. 1
Occurrence	1 .. 1
Type	sharedelements:PaymentTerms
Type	xs:string
Use	required
General Notes	PAYMENT TERMS TYPE
Applicable Codes	
ContractBasis	Contract Basis
DatingGiven	Dating Given
EndOfMonth	End of Month
FixedDate	Fixed Date
PreviouslyAgreedUpon	Previously Agreed Upon
Occurrence	1 .. 1
Occurrence	0 .. 1
Type	xs:string
General Notes	PAYMENT TERMS DESCRIPTION
PeriodType	
Occurrence	0 .. 1
Type	xs:string
General Notes	PERIOD TYPE
Applicable Codes	
Day	Day
Month	Month
Occurrence	0 .. 1
Type	xs:string
General Notes	PERIOD COUNT

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
Dates	Occurrence 0 .. 1 Type <i>invoice:DateList</i> General Notes PAYMENT TERMS DATES Examples <Dates> <Date Type="TermsNetDue" Format="DateTime"> <DateTime>20200213</DateTime> </Date> </Dates>
xs:sequence	Occurrence 1 .. 1
Date	Occurrence 0 .. unbounded Type <i>sharedelements:Date</i> Type <i>xs:string</i> Use required General Notes PAYMENT DATE TYPE Applicable Codes TermsNetDue Terms net due date Type <i>xs:string</i> Use required General Notes PAYMENT DATE FORMAT Applicable Codes Date YYYYMMDD DateTime YYYYMMDDHHMM
Format	
xs:sequence	Occurrence 1 .. 1
DateTime	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes PAYMENT DATE / TIME
TransportStages	Occurrence 0 .. 1 Type <i>invoice:TransportStageList</i> General Notes INVOICE TRANSPORT STAGES
xs:sequence	Occurrence 1 .. 1
TransportStage	Occurrence 0 .. unbounded Type <i>invoice:TransportStage</i> xs:sequence 1 .. 1 Occurrence 0 .. 1 Type <i>sharedelements:Stage</i> General Notes TRANSPORTATION STAGE Examples <Stage Type="MainCarriage"> <ModeOfTransport>Sea</ModeOfTransport> <TransportId>017W</TransportId> <CarrierId>12345678</CarrierId> <CarrierName>Carrier line</CarrierName> <TransportType>Main</TransportType> <TransportMeansName>Vesselname</TransportMeansName> </Stage>
Stage	
xs:sequence	Occurrence 1 .. 1
Type	Type <i>xs:string</i> Use required General Notes TRANSPORTATION STAGE TYPE Applicable Codes MainCarriage Main Carriage PlannedLeg1 Main carriage - first carrier PlannedLeg2 Main carriage - second carrier

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	Applicable Codes
PlannedLeg3	Main carriage - third carrier
PlannedLeg4	Main carriage - fourth carrier
PlannedLeg5	Main carriage - fifth carrier
xs:sequence	Occurrence 1 .. 1
ModeOfTransport	Occurrence 0 .. 1
	Type xs:string
	General Notes MODE OF TRANSPORTATION
	Applicable Codes
	Air Air transportation
	Road Road transportation
	Sea Sea transportation
TransportId	Occurrence 0 .. 1
	Type xs:string
	General Notes TRANSPORT IDENTIFICATION
CarrierId	Occurrence 0 .. 1
	Type xs:string
	General Notes CARRIER IDENTIFICATION
	Air & Sea: DSV carrier identifier
	Road: Not used
CarrierName	Occurrence 0 .. 1
	Type xs:string
	General Notes CARRIER NAME
	Road: Not used
TransportType	Occurrence 0 .. 1
	Type xs:string
	General Notes TRANSPORT TYPE
	Road: Not used
TransportMeansName	Occurrence 0 .. 1
	Type xs:string
	General Notes TRANSPORT MEANS NAME
	Sea: Vessel Name
	Air & Road: Not used
TransportServices	Occurrence 0 .. 1
	Type invoice:TransportServiceList
	General Notes TRANSPORTATION STAGE SERVICES REQUIRED
	Examples
	<TransportServices>
	<TransportService>
	<ServiceCode>LSE</ServiceCode>
	</TransportService>
	</TransportServices>
xs:sequence	Occurrence 1 .. 1
TransportService	Occurrence 0 .. unbounded
	Type sharedelements:TransportService
xs:sequence	Occurrence 1 .. 1
ServiceCode	Occurrence 0 .. 1
	Type xs:string
	General Notes TYPE OF SERVICE REQUIRED
	Applicable Codes
	Before10 Express 10:00
	Before12 Express 12:00
	Before16 Express 16:00
	Before7 Express 07:00

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	Applicable Codes
	Crane Crane required loading or unloading or both
	FCL Full Container Load
	FTL Full Truckload
	HAZ Hazardous goods
	IATA Air - IATA
	InNightproduct InNight product
	LCL Less Than Container Load
	LSE Air - LSE
	LTL Less Than Truckload
	Lift Tail lift
	Notification Notify
	OMEX Omex service goods
	PersonalDeliveryService Personal delivery service
	PreAdvice Pre-advice
	ePallet E-service pallet
	eParcel E-service parcel
PriorityCode	Occurrence 0 .. 1 Type xs:string General Notes SERVICE PRIORITY CODE Only provided for Main Service (First TransportService)
	Applicable Codes
	Express Express Service
	HighSpeed High Speed Service
	Normal Normal Service
Locations	Occurrence 0 .. 1 Type invoice:LocationGroupList General Notes TRANSPORTATION STAGE LOCATIONS
	Examples
	<pre> <Locations> <LocationGroup> <Location Type="PlaceOfLoading" > <LocationIdentification></LocationIdentification> </Location> <Dates> <Date Type="DepartureLoading" Format="DateTime" > <DateTime>201911230000</DateTime> </Date> </Dates> </LocationGroup> <LocationGroup> <Location Type="Destination" > <LocationIdentification></LocationIdentification> </Location> <Dates> <Date Type="EstimatedArrival" Format="DateTime" > <DateTime>201911250000</DateTime> </Date> <Date Type="ActualArrival" Format="DateTime" > <DateTime>201911250000</DateTime> </Date> </Dates> </LocationGroup> </Locations> </LocationIdentification> </Location> </Locations> </pre>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
xs:sequence	Occurrence 1 .. 1
LocationGroup	Occurrence 0 .. unbounded Type invoice:LocationGroup
xs:sequence	Occurrence 1 .. 1
Location	Occurrence 0 .. 1 Type sharedelements:Location
Type	Type xs:string Use required General Notes TRANSPORTATION LOCATION TYPE
Applicable Codes	
Departure	Place of Departure
Destination	Place of Destination
PlaceOfLoading	Place of Loading
PlaceOfUnloading	Place of Unloading
xs:sequence	Occurrence 1 .. 1
LocationIdentification	Occurrence 1 .. unbounded Type sharedelements:LocationIdentification
Type	Type xs:string General Notes LOCATION IDENTIFIER TYPE
Applicable Codes	
GS1	GS1
IATA	IATA
UN	UN
xs:sequence	Occurrence 1 .. 1
LocationIdentifier	Occurrence 0 .. 1 Type xs:string General Notes LOCATION IDENTIFIER
LocationName	Occurrence 0 .. 1 Type xs:string General Notes LOCATION NAME
Dates	Occurrence 0 .. 1 Type invoice:DateList General Notes TRANSPORTATION LOCATION DATES
Examples	
<Dates>	
<Date Type="DepartureLoading" Format="DateTime" >	
<DateTime>201911230000</DateTime>	
</Date>	
</Dates>	
<Dates>	
<Date Type="EstimatedArrival" Format="DateTime" >	
<DateTime>201911250000</DateTime>	
</Date>	
<Date Type="ActualArrival" Format="DateTime" >	
<DateTime>201911250000</DateTime>	
</Date>	
</Dates>	
xs:sequence	Occurrence 1 .. 1
Date	Occurrence 0 .. unbounded Type sharedelements:Date
Type	Type xs:string Use required General Notes TRANSPORT DATE TYPE
Applicable Codes	
ActualArrival	Transport means arrival date time, actual

Bold = Element, Italic = Attribute, Grey = Group

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
Examples <TermsOfDelivery> <Terms> <TermCode>CIP</TermCode> <CodeId>IncoTerms</CodeId> </Terms> <Location Type="NamedPlace"> <LocationIdentification Type="UN"> <LocationIdentifier>DKCPH</LocationIdentifier> <LocationName>Copenhagen</LocationName> </LocationIdentification> </Location> </TermsOfDelivery>	
xs:sequence	Occurrence 1 .. 1
Terms	Occurrence 0 .. 1
	Type <i>sharedElements:Terms</i>
xs:sequence	Occurrence 1 .. 1
TermCode	Occurrence 0 .. 1
	Type <i>xs:string</i>
	General Notes TERM CODE
CodeId	Occurrence 0 .. 1
	Type <i>xs:string</i>
	General Notes TYPE OF TERM CODE
Applicable Codes CombiTerms Combi Terms IncoTerms INCO Terms	
Location	Occurrence 0 .. unbounded
	Type <i>sharedElements:Location</i>
	General Notes TERMS OF DELIVERY LOCATION
Type	Type <i>xs:string</i>
	Use required
	General Notes TERM LOCATION TYPE
Applicable Codes NamedPlace Named Place	
xs:sequence	Occurrence 1 .. 1
LocationIdentification	Occurrence 1 .. unbounded
	Type <i>sharedElements:LocationIdentification</i>
xs:sequence	Occurrence 1 .. 1
LocationName	Occurrence 0 .. 1
	Type <i>xs:string</i>
	General Notes LOCATION NAME
EquipmentUnits	Occurrence 0 .. 1
	Type <i>invoice:EquipmentUnitList</i>
	General Notes INVOICE EQUIPMENT INFORMATION
Examples For containerized sea freight: <EquipmentUnit> <EquipmentType> <Type>Container</Type> <UnitId>MSCU1234567</UnitId> <SizeTypeCode>40GP</SizeTypeCode> </EquipmentType> <SealIds>	

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
Examples <Seal> <SealId>Seal1</SealId> </Seal> </SealIds> </EquipmentUnit>	
xs:sequence	Occurrence 1 .. 1
EquipmentUnit	Occurrence 0 .. unbounded Type invoice:EquipmentUnit General Notes EQUIPMENTUNIT
xs:sequence	Occurrence 1 .. 1
EquipmentType	Occurrence 0 .. 1 Type sharedelements:EquipmentType General Notes EQUIPMENT TYPE INFORMATION
xs:sequence	Occurrence 1 .. 1
Type	Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT TYPE
Applicable Codes Container Shipping Container EFP Euro Flat Pallet EUR Euro Pallet Trailer Trailer	
UnitId	Occurrence 0 .. 1 Type xs:string General Notes INVOICE CONTAINER NUMBER
SizeTypeCode	Occurrence 0 .. 1 Type xs:string General Notes CONTAINER SIZE AND TYPE DSV specified Container Type for Shipping Container
Applicable Codes 20GP 20 ft General Purpose 20RE 20 ft Reefer 40GP 40 ft General Purpose 40HC 40 ft High Cube 40NOR 40 ft high Cube, self powered Reefer 40RE 40 ft Reefer 40REHC 40 ft High Cube Reefer	
PackingMode	Occurrence 0 .. 1 Type xs:string General Notes PACKINGMODE
Applicable Codes BBK Break Bulk - BBK BCN Buyer's Consolidation - BCN FCL Full, single consignment - FCL GRP Groupage - GRP LCL Full, mixed consignment - LCL ROR Roll on/Roll off - ROR	
SealIds	Occurrence 0 .. 1 Type invoice:SealList General Notes SEAL IDS
xs:sequence	Occurrence 1 .. 1
Seal	Occurrence 0 .. unbounded Type sharedelements:Seal

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
General Notes	SEAL
xs:sequence	Occurrence 1 .. 1
SealId	Occurrence 0 .. 1
	Type xs:string
General Notes	SEAL NUMBER
InvoiceLines	Occurrence 0 .. 1
	Type invoice:InvoiceLinesList
General Notes	INVOICE LINES
xs:sequence	Occurrence 1 .. 1
InvoiceLine	Occurrence 0 .. unbounded
	Type invoice:LinItem
General Notes	INVOICE LINE
xs:sequence	Occurrence 1 .. 1
LinItem	Occurrence 0 .. 1
	Type sharedelements:InvoiceLine
General Notes	INVOICE LINE IDENTIFIERS
Examples	
<LinItem> <LinItemNumber>1</LinItemNumber> <ItemIdentifier>ABCD1234567</ItemIdentifier> </LinItem>	
xs:sequence	Occurrence 1 .. 1
LinItemNumber	Occurrence 0 .. 1
	Type xs:string
General Notes	LINE ITEM NUMBER
ItemIdentifier	Occurrence 0 .. 1
	Type xs:string
General Notes	ITEM IDENTIFIER
ItemDescriptions	Occurrence 0 .. 1
	Type invoice:ItemDescriptionList
General Notes	LINE ITEM DESCRIPTIONS
Examples	
<ItemDescriptions> <ItemDescription DescriptionFormatCode="Semi-Structured" > <ItemCharacteristicCode>1</ItemCharacteristicCode> <ItemDescription>AES Filing Fee</ItemDescription> </ItemDescription> <ItemDescription DescriptionFormatCode="Semi-Structured" > <ItemCharacteristicCode>2</ItemCharacteristicCode> <ItemDescription>Pick up/ Collection</ItemDescription> </ItemDescription> <ItemDescription DescriptionFormatCode="Semi-Structured" > <ItemCharacteristicCode>8</ItemCharacteristicCode> <ItemDescription>Inland/Linehaul/Haulage</ItemDescription> </ItemDescription> <ItemDescription DescriptionFormatCode="Semi-Structured" > <ItemCharacteristicCode>9</ItemCharacteristicCode> <ItemDescription>THC (Terminal Handling Charge) Import</ItemDescription> </ItemDescription> </ItemDescriptions>	
xs:sequence	Occurrence 1 .. 1

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation														
ItemDescription	Occurrence 0 .. unbounded Type <i>sharedelements:ItemDescription</i> General Notes ITEM DESCRIPTION														
DescriptionFormatCode	Type xs:string Use required General Notes DESCRIPTION FORMAT CODE Applicable Codes Semi-Structured Semi-Structured														
xs:sequence	Occurrence 1 .. 1														
ItemCharacteristicCode	Occurrence 0 .. 1 Type xs:string General Notes ITEM CHARACTERISTIC CODE														
ItemDescription	Occurrence 0 .. 1 Type xs:string General Notes ITEM DESCRIPTION														
Measurements	Occurrence 0 .. 1 Type <i>invoice:MeasurementList</i> General Notes LINE ITEM MEASUREMENTS Examples <pre> <Measurements> <Measurement Type="GrossWeight" Uom="KGM"> <Measure>10.03</Measure> </Measurement> <Measurement Type="NetWeight" Uom="KGM"> <Measure>8.03</Measure> </Measurement> <Measurement Type="Volume" Uom="MTQ"> <Measure>2.03</Measure> </Measurement> <Measurement Type="LoadingMeters" Uom="MTR"> <Measure>2.05</Measure> </Measurement> <Measurement Type="PalletSpaces" Uom="PLL"> <Measure>5</Measure> </Measurement> </Measurements> </pre>														
xs:sequence	Occurrence 1 .. 1														
Measurement	Occurrence 0 .. unbounded Type <i>sharedelements:Measurement</i> General Notes MEASUREMENT														
Type	Type xs:string Use required General Notes MEASUREMENT TYPE Applicable Codes <table> <tr> <td>ChargeableWeight</td><td>Chargeable weight</td></tr> <tr> <td>ConsignmentGrossWeight</td><td>Consignment gross weight</td></tr> <tr> <td>GrossWeight</td><td>Gross weight</td></tr> <tr> <td>LoadingMeters</td><td>Loading Meters</td></tr> <tr> <td>NetWeight</td><td>Net weight</td></tr> <tr> <td>PalletSpaces</td><td>Pallet Spaces</td></tr> <tr> <td>Volume</td><td>Volume</td></tr> </table>	ChargeableWeight	Chargeable weight	ConsignmentGrossWeight	Consignment gross weight	GrossWeight	Gross weight	LoadingMeters	Loading Meters	NetWeight	Net weight	PalletSpaces	Pallet Spaces	Volume	Volume
ChargeableWeight	Chargeable weight														
ConsignmentGrossWeight	Consignment gross weight														
GrossWeight	Gross weight														
LoadingMeters	Loading Meters														
NetWeight	Net weight														
PalletSpaces	Pallet Spaces														
Volume	Volume														
Uom	Type xs:string General Notes MEASUREMENT UNIT OF MEASURE														

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
xs:sequence Measure	Occurrence 1 .. 1 Occurrence 0 .. 1 Type <i>xs:string</i> General Notes MEASUREMENT
Dates	Occurrence 0 .. 1 Type <i>invoice:DateList</i> General Notes INVOICE LINE DATES Examples <Dates> <Date Type="EstimatedCollection" Format="Date Time" > <DateTime>202001240000</DateTime> </Date> </Dates>
xs:sequence Date	Occurrence 1 .. 1 Occurrence 0 .. unbounded Type <i>sharedelements:Date</i> General Notes DATE
Type	Type <i>xs:string</i> Use required General Notes INVOICE LINE DATE TYPE Applicable Codes ActualArrival Transport means arrival date time, actual ActualCollection Collection date/time, latest ActualDelivery Delivery date/time, actual ActualDeparture Transport means departure date/time, actual CargoPickup Cargo pick-up date / time Collection Collection date/time, earliest ConsignmentLoading Consignment loading date time DeliveryRequested Delivery Requested EstimatedDelivery Delivery date/time, estimated ScheduledArrival Scheduled Arrival ScheduledDelivery Delivery date/time, 1st schedule ScheduledDeparture Scheduled Departure ScheduledShipmentArrival Completion date or time, scheduled ScheduledShipmentDeparture Start date or time, scheduled ShipmentReqDate Shipment requested date/time
Format	Type <i>xs:string</i> Use required General Notes INVOICE LINE DATE FORMAT Applicable Codes Date YYYYMMDD DateTime YYYYMMDDHHMM DateTimeInterval YYYYMMDDHHMM-YYYYMMDDHHMM
xs:sequence DateTime	Occurrence 1 .. 1 Occurrence 0 .. 1 Type <i>xs:string</i> General Notes INVOICE LINE DATE / TIME
EquipmentUnits	Occurrence 0 .. 1 Type <i>invoice:EquipmentUnitList</i> General Notes INVOICE LINE EQUIPMENT INFORMATION Examples <EquipmentUnits> <EquipmentUnit> <EquipmentType>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
Examples <Type>Container</Type> <UnitId>TCLU8092315</UnitId> <SizeTypeCode>45G1</SizeTypeCode> <ISOCODE>ISOCODEEQD</ISOCODE> <PackingMode>FCL</PackingMode> </EquipmentType> </EquipmentUnit> </EquipmentUnits>	
xs:sequence EquipmentUnit	Occurrence 1 .. 1 Occurrence 0 .. unbounded Type invoice:EquipmentUnit General Notes EQUIPMENT UNIT DETAILS
xs:sequence EquipmentType	Occurrence 1 .. 1 Occurrence 0 .. 1 Type sharedelements:EquipmentType General Notes EQUIPMENT TYPE INFORMATION
xs:sequence Type	Occurrence 1 .. 1 Occurrence 0 .. 1 Type xs:string General Notes EQUIPMENT TYPE
Applicable Codes	
Container	Ocean Container
EFP	Euro Flat Pallet
EUR	Euro Pallet
Trailer	Trailer
UnitId	Occurrence 0 .. 1 Type xs:string General Notes SHIPPING CONTAINER NUMBER
SizeTypeCode	Occurrence 0 .. 1 Type xs:string General Notes CONTAINER SIZE AND TYPE DSV specified Container Type for Shipping Container
Applicable Codes	
20GP	20 ft General Purpose
20RE	20 ft Reefer
40GP	40 ft General Purpose
40HC	40 ft High Cube
40NOR	40 ft high Cube, self powered Reefer
40RE	40 ft Reefer
40REHC	40 ft High Cube Reefer
ISOCODE	Occurrence 0 .. 1 Type xs:string General Notes SHIPPING CONTAINER ISO CODE
PackingMode	Occurrence 0 .. 1 Type xs:string General Notes CONTAINER PACKING MODE
Applicable Codes	
BBK	Break Bulk - BBK
BCN	Buyer's Consolidation - BCN
FCL	Full, single consignment - FCL
GRP	Groupage - GRP
LCL	Full, mixed consignment - LCL
ROR	Roll on/Roll off - ROR

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation						
FreeTextData	Occurrence 0 .. 1 Type <i>invoice:FreeTextList</i> General Notes INVOICE LINE FREE TEXT DATA Examples <pre> <FreeTextData> <FreeText Type="GoodsDescription" > <TextLine1>ENGINE UNDERDECK</TextLine1> </FreeText> <FreeText Type="ServiceCharacteristic" > <TextLine1>BCN</TextLine1> </FreeText> <FreeText Type="OtherServiceInformation" > <TextLine1>OSI1</TextLine1> <TextLine2>OSI2</TextLine2> <TextLine3>OS3</TextLine3> <TextLine4>OS4</TextLine4> <TextLine5>OS5</TextLine5> </FreeText> </FreeTextData> </pre>						
xs:sequence	Occurrence 1 .. 1						
FreeText	Occurrence 0 .. unbounded Type <i>sharedelements:FreeText</i>						
Type	Type <i>xs:string</i> Use required General Notes FREE TEXT TYPE Applicable Codes <table> <tr> <td>GoodsDescription</td><td>Goods Description</td></tr> <tr> <td>OtherServiceInformation</td><td>Other Service Information</td></tr> <tr> <td>ServiceCharacteristic</td><td>Service Characteristic</td></tr> </table>	GoodsDescription	Goods Description	OtherServiceInformation	Other Service Information	ServiceCharacteristic	Service Characteristic
GoodsDescription	Goods Description						
OtherServiceInformation	Other Service Information						
ServiceCharacteristic	Service Characteristic						
xs:sequence	Occurrence 1 .. 1						
TextLine1	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes FREE TEXT LINE 1						
TextLine2	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes FREE TEXT LINE 2						
MonetaryAmounts	Occurrence 0 .. 1 Type <i>invoice:MonetaryAmountList</i> General Notes INVOICE LINE MONETARY AMOUNTS Examples <pre> <MonetaryAmounts> <MonetaryAmount Type="TotalAmount" > <Amount>467.5</Amount> <Currency>EUR</Currency> <CurrencyType>InvoicingCurrency</CurrencyType> </MonetaryAmount> <MonetaryAmount Type="TaxableAmount" > <Amount>374</Amount> <Currency>EUR</Currency> <CurrencyType>InvoicingCurrency</CurrencyType> </MonetaryAmount> </MonetaryAmounts> </pre>						
xs:sequence	Occurrence 1 .. 1						
MonetaryAmount	Occurrence 0 .. unbounded Type <i>sharedelements:MonetaryAmount</i>						

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	General Notes <i>MONETARY AMOUNT</i>
Type	Type <i>xs:string</i> Use required
	General Notes <i>MONETARY AMOUNT TYPE</i>
	Applicable Codes
TaxableAmount	Taxable Amount
TotalAmount	Total Line Item Amount
xs:sequence	Occurrence 1 .. 1
Amount	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes <i>MONETARY AMOUNT</i>
Currency	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes <i>MONETARY AMOUNT CURRENCY</i>
CurrencyType	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes <i>MONETARY CURRENCY TYPE</i>
	Applicable Codes
InvoicingCurrency	Invoicing Currency
References	Occurrence 0 .. 1 Type <i>invoice:ReferenceGroupList</i> General Notes <i>INVOICE LINE REFERENCES</i>
	Examples
	<pre> <References> <ReferenceGroup> <Reference Type="Shipper Reference">S42900531</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="ConsigneeReference">C42900281</Reference> </ReferenceGroup> <ReferenceGroup> <Reference Type="RoadWaybill">7112233190</Reference> </ReferenceGroup> </References> </pre>
xs:sequence	Occurrence 1 .. 1
ReferenceGroup	Occurrence 0 .. unbounded Type <i>invoice:ReferenceGroup</i> General Notes <i>REFERENCE GROUP</i>
xs:sequence	Occurrence 1 .. 1
Reference	Occurrence 0 .. 1 Type <i>sharedElements:Reference</i> General Notes <i>INVOICE LINE REFERENCE</i>
Type	Type <i>xs:string</i> Use required General Notes <i>INVOICE LINE REFERENCE TYPE</i>
	Applicable Codes
AgentsReference	Agent's reference
AirWayBill	Air waybill number
CargoManifestNo	Cargo manifest number, Transport Id
ConsigneeOrderNumber	Consignee's order number
ConsigneeReference	Consignee Reference
ConsignmentId	Consignment id, carrier assigned
CustomField	Custom Field

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
Applicable Codes	
CustomerReferenceNumber	Customer reference number
DeliveryAgreement	Delivery Agreement
DocumentReference	Document Reference
ExternalReference	External reference customer reference number
GINCNumber	Waybill number, GINC
HouseBill	House bill of lading number
MasterBill	Master bill of lading number
OrderReference	Order Reference
PackageNumber	Package Number
ProofOfDeliveryNumber	Proof of delivery reference number
RoadWaybill	Road Waybill number, SIS
ShipmentReference	Shipment reference number
ShipperReference	Shipper Reference
TransportInstructionNumber	Transport instruction number
VehicleId	Vehicle identification number (VIN)
VesselCountryOfRegistration	Vessel Country of Registration
VesselId	Vessel identifier
Packages	Occurrence 0 .. 1 Type <i>invoice:PackageGroupList</i> General Notes INVOICE LINE PACKAGE DETAILS
Examples	
<pre> <Packages> <PackageGroup> <Package> <PackageQuantity>1</PackageQuantity> <PackageCode>PLL</PackageCode> </Package> <PackageId> <InstructionCode>PackageMarks</InstructionCode> <Marks> <ShippingMark>Line16416416416416416</ShippingMark> </Marks> </PackageId> </PackageGroup> </Packages> </pre>	
xs:sequence	Occurrence 1 .. 1
PackageGroup	Occurrence 0 .. unbounded Type <i>invoice:PackageGroup</i> General Notes PACKAGE GROUP
xs:sequence	Occurrence 1 .. 1
Package	Occurrence 0 .. 1 Type <i>shardelements:Package</i> General Notes PACKAGE
xs:sequence	Occurrence 1 .. 1
PackageQuantity	Occurrence 1 .. 1 Type <i>xs:string</i> General Notes PACKAGE QUANTITY
PackageCode	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes PACKAGE CODE
PackageId	Occurrence 0 .. 1 Type <i>shardelements:PackageId</i> General Notes PACKAGE ID

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
xs:sequence	Occurrence 1 .. 1
InstructionCode	Occurrence 1 .. 1 Type xs:string General Notes PACKAGE INSTRUCTION TYPE
	Applicable Codes
	PackageMarks Package Marks and Numbers
Marks	Occurrence 0 .. 1 Type sharedelements:Marks General Notes MARKS
xs:sequence	Occurrence 1 .. 1
ShippingMark	Occurrence 1 .. unbounded Type xs:string General Notes PACKAGE SHIPPING MARK
Locations	Occurrence 0 .. 1 Type invoice:LocationGroupList General Notes INVOICE LINE LOCATIONS
	Examples
	<pre> <Locations> <LocationGroup> <Location Type="PlaceOfLoading" > <LocationIdentification Type="IATA" > <LocationIdentifier>LineCAMTR</LocationIdentifier> <LocationName>LineMontreal</LocationName> </LocationIdentification> <LocationIdentification Type="IATA" > <LocationIdentifier>LineCAMTR</LocationIdentifier> <LocationName>LineMontreal</LocationName> </LocationIdentification> </Location> </LocationGroup> <LocationGroup> <Location Type="PlaceOfUnloading" > <LocationIdentification> <LocationIdentifier>LineGBSOU</LocationIdentifier> <LocationName>LineSouthampton</LocationName> </LocationIdentification> </Location> </LocationGroup> </Locations> </pre>
xs:sequence	Occurrence 1 .. 1
LocationGroup	Occurrence 0 .. unbounded Type invoice:LocationGroup General Notes LOCATION GROUP
xs:sequence	Occurrence 1 .. 1
Location	Occurrence 0 .. 1 Type sharedelements:Location General Notes INVOICE LINE LOCATION
Type	Type xs:string Use required General Notes LOCATION TYPE
	Applicable Codes
	Departure Place of Departure
	Destination Place of Destination
	PlaceOfLoading Place of Loading

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	Applicable Codes
	PlaceOfUnloading Place of Unloading
xs:sequence	Occurrence 1 .. 1
LocationIdentification	Occurrence 1 .. unbounded
	Type sharedelements:LocationIdentification
	General Notes LOCATION IDENTIFICATION
Type	Type xs:string
	General Notes LOCATION IDENTIFIER TYPE
	Applicable Codes
	GS1 GS1
	IATA IATA
	UN UN
xs:sequence	Occurrence 1 .. 1
LocationIdentifier	Occurrence 0 .. 1
	Type xs:string
	General Notes LOCATION IDENTIFIER
LocationName	Occurrence 0 .. 1
	Type xs:string
	General Notes LOCATION NAME
Taxes	Occurrence 0 .. 1
	Type invoice:TaxGroupList
	General Notes INVOICE LINE TAX DETAILS
	Examples
	<pre> <Taxes> <TaxDetails> <Tax Type="Tax" > <TaxRate>1.000</TaxRate> <TaxCode>ValueAddedTax</TaxCode> <TaxCategory>ZeroRatedGoods</TaxCategory> </Tax> <MonetaryAmounts> <MonetaryAmount Type="TaxAmount" > <Amount>0.2</Amount> <Currency>SEK</Currency> <CurrencyType>HomeCurrency</CurrencyType> </MonetaryAmount> </MonetaryAmounts> </TaxDetails> </Taxes> </pre>
xs:sequence	Occurrence 1 .. 1
TaxDetails	Occurrence 0 .. unbounded
	Type invoice:TaxGroup
	General Notes TAX DETAILS
xs:sequence	Occurrence 1 .. 1
Tax	Occurrence 0 .. 1
	Type sharedelements:Tax
	General Notes INVOICE LINE TAX
Type	Type xs:string
	Use required
	General Notes TAX TYPE
	Applicable Codes
	Tax Tax
xs:sequence	Occurrence 1 .. 1

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
TaxRate	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes TAX RATE
TaxCode	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes TAX CODE Applicable Codes ValueAddedTax ValueAddedTax
TaxCategory	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes TAX CATEGORY Applicable Codes ExemptTax Exempt from tax MixedTaxRate Mixed tax rate StandardRate Standard rate VATReverseCharge VAT Reverse Charge ZeroRatedGoods Zero rated goods
MonetaryAmounts	Occurrence 0 .. 1 Type <i>invoice:MonetaryAmountList</i> General Notes TAX MONETARY AMOUNTS Examples <MonetaryAmounts> <MonetaryAmount Type="TaxAmount" > <Amount>0.2</Amount> <Currency>EUR</Currency> <CurrencyType>HomeCurrency</CurrencyType> </MonetaryAmount> </MonetaryAmounts>
xs:sequence	Occurrence 1 .. 1
MonetaryAmount	Occurrence 0 .. unbounded Type <i>sharedElements:MonetaryAmount</i> General Notes MONETARY AMOUNT
Type	Type <i>xs:string</i> Use required General Notes MONETARY AMOUNT TYPE Applicable Codes TaxAmount Tax Amount
xs:sequence	Occurrence 1 .. 1
Amount	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes MONETARY AMOUNT
Currency	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes MONETARY AMOUNT ISO CURRENCY CODE
CurrencyType	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes MONETARY AMOUNT CURRENCY TYPE Applicable Codes InvoicingCurrency Invoicing Currency
Parties	Occurrence 0 .. 1 Type <i>invoice:PartiesList</i> General Notes INVOICE LINE PARTIES

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
Examples <pre> <Parties> <Party> <PartyDetails Role="Consignor" > <Id>1234567890</Id> <PartyName>Consignor</PartyName> <AddressLine1>Street</AddressLine1> <CityName>City</CityName> <PostCode>123 45</PostCode> <CountryCode>SE</CountryCode> </PartyDetails> </Party> <Party> <PartyDetails Role="Despatch" > <Id>1234567890</Id> <PartyName>Consignor</PartyName> <AddressLine1>Street</AddressLine1> <CityName>City</CityName> <PostCode>123 45</PostCode> <CountryCode>SE</CountryCode> </PartyDetails> </Party> <Party> <PartyDetails Role="Consignee" > <Id>9876543210</Id> <PartyName>Consignee</PartyName> <AddressLine1>Street 1</AddressLine1> <AddressLine2>Street 2</AddressLine2> <CityName>City</CityName> <PostCode>678 90</PostCode> <CountryCode>AE</CountryCode> </PartyDetails> </Party> </Parties> </pre>	
xs:sequence	Occurrence 1 .. 1
Party	Occurrence 0 .. unbounded
	Type invoice:Party
xs:sequence	Occurrence 1 .. 1
PartyDetails	Occurrence 0 .. 1
	Type sharedelements:PartyDetails
	General Notes INVOICE LINE PARTY DETAILS
Role	Type xs:string
	Use required
	General Notes PARTY ROLE
Applicable Codes	
Carrier	Carrier Party
Consignee	Consignee Party
Consignor	Consignor Party
Consolidator	Consolidator
Deconsolidator	Deconsolidator
Delivery	Delivery Party
DeliveryAgent	Delivery Agent
DeliveryLocalCartage	Delivery Local Cartage
Despatch	Despatch Party
Forwarder	Forwarder
FreightForwarder	Freight Forwarder
FreightPayer	Freight/charges Payer
Notify	Notify Party

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	Applicable Codes
	OrderingCustomer Ordering Customer
	PickupAgent Pickup Agent
	PickupLocalCartage Pickup Local Cartage
	ShipFrom Ship From
	ShipTo Ship To
	Supplier Supplier
xs:sequence	Occurrence 1 .. 1
Id	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY IDENTIFIER
PartyName	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY NAME
AddressLine1	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY ADDRESS LINE 1
AddressLine2	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY ADDRESS LINE 2
AddressLine3	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY ADDRESS LINE 3
CityName	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY ADDRESS CITY NAME
State	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY ADDRESS STATE / PROVINCE
PostCode	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY ADDRESS POST OR ZIP CODE
CountryCode	Occurrence 0 .. 1
	Type xs:string
	General Notes PARTY ADDRESS ISO COUNTRY CODE
AllowancesorCharges	Occurrence 0 .. 1
	Type invoice:AllowancesorChargesGroupList
	General Notes INVOICE LINE ALLOWANCES AND CHARGES
xs:sequence	Occurrence 1 .. 1
AllowanceOrChargeGroup	Occurrence 0 .. unbounded
	Type invoice:AllowanceOrChargeGroup
	Examples
	<pre> <AllowanceOrChargeGroup> <AllowanceOrCharge AllowanceOrChargeCode="Charge" > <AllowanceOrChargeIdentifier>FRT</AllowanceOrChargeIdentifier> <SpecialServiceDescription>Freight</SpecialServiceDescription> </AllowanceOrCharge> <MonetaryAmounts> <MonetaryAmountGroup> <MonetaryAmount Type="AllowanceorChargeAmount" > <Amount>1067193</Amount> <Currency>JPY</Currency> <CurrencyType>InvoicingCurrency</CurrencyType> </MonetaryAmount> </MonetaryAmountGroup> </MonetaryAmounts> </AllowanceOrChargeGroup> </pre>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	Examples <pre> </MonetaryAmount> </MonetaryAmountGroup> <MonetaryAmountGroup> <MonetaryAmount Type="DestinationCurrency" > <Amount>1067193</Amount> <Currency>JPY</Currency> <CurrencyType>HomeCurrency</CurrencyType> </MonetaryAmount> </MonetaryAmountGroup> <MonetaryAmountGroup> <MonetaryAmount Type="ChargeCurrency" > <Amount>8132.85</Amount> <Currency>EUR</Currency> </MonetaryAmount> <Currencies> <CurrencyDetails> <Currency> <CurrencyUsage>ReferenceCurrency</CurrencyUsage> <CurrencyIdentification>JPY</CurrencyIdentification> <CurrencyCode>InvoicingCurrency</CurrencyCode> <CurrencyRate>0.0076</CurrencyRate> </Currency> </CurrencyDetails> </Currencies> </MonetaryAmountGroup> </MonetaryAmounts> <Taxes> <TaxDetails> <Tax Type="Tax" > <TaxRate>0.000</TaxRate> <TaxCode>ValueAddedTax</TaxCode> <TaxCategory>ZeroRatedGoods</TaxCategory> </Tax> <MonetaryAmounts> <MonetaryAmount Type="TaxAmount" > <Amount>0</Amount> <Currency>JPY</Currency> <CurrencyType>InvoicingCurrency</CurrencyType> </MonetaryAmount> <MonetaryAmount Type="TaxAmount" > <Amount>0</Amount> <Currency>JPY</Currency> <CurrencyType>HomeCurrency</CurrencyType> </MonetaryAmount> </MonetaryAmounts> </TaxDetails> </Taxes> <Rate Type="SystemExchangeRate" >131.221235</Rate> </AllowanceOrChargeGroup> </pre>
xs:sequence	Occurrence 1 .. 1
AllowanceOrCharge	Occurrence 0 .. 1
	Type shared elements: AllowanceOrCharge
	General Notes ALLOWANCE OR CHARGE DETAILS
	Examples <pre> <AllowancesOrCharges> <AllowanceOrChargeGroup> <AllowanceOrCharge AllowanceOrChargeCode="Charge" > </pre>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	Examples <AllowanceOrChargeIdentifier>FRT</AllowanceOrChargeIdentifier> <SpecialServiceDescription>Freight</SpecialServiceDescription> </AllowanceOrCharge>
AllowanceOrChargeCode	Type xs:string Use required General Notes ALLOWANCE OR CHARGE CODE Applicable Codes Allowance Allowance Charge Charge
xs:sequence	Occurrence 1 .. 1
AllowanceOrChargeIdentifier	Occurrence 0 .. 1 Type xs:string General Notes ALLOWANCE OR CHARGE IDENTIFIER
SpecialServiceDescriptionCode	Occurrence 0 .. 1 Type xs:string General Notes SPECIAL SERVICE DESCRIPTION CODE
SpecialServiceDescription	Occurrence 0 .. 1 Type xs:string General Notes SPECIAL SERVICE DESCRIPTION
MonetaryAmounts	Occurrence 0 .. 1 Type invoice:MonetaryAmountGroupList General Notes ALLOWANCE OR CHARGE MONETARY AMOUNTS Examples <MonetaryAmounts> <MonetaryAmountGroup> <MonetaryAmount Type="AllowanceorChargeAmount"> <Amount>62.88</Amount> <Currency>USD</Currency> <CurrencyType>InvoicingCurrency</CurrencyType> </MonetaryAmount> </MonetaryAmountGroup> <MonetaryAmountGroup> <MonetaryAmount Type="DestinationCurrency"> <Amount>51.41</Amount> <Currency>GBP</Currency> <CurrencyType>HomeCurrency</CurrencyType> </MonetaryAmount> <Currencies> <CurrencyDetails> <Currency> <CurrencyUsage>ReferenceCurrency</CurrencyUsage> <CurrencyIdentification>USD</CurrencyIdentification> <CurrencyCode>InvoicingCurrency</CurrencyCode> <CurrencyRate>0.8176</CurrencyRate> </Currency> </CurrencyDetails> </Currencies> </MonetaryAmountGroup> </MonetaryAmounts>
xs:sequence	Occurrence 1 .. 1
MonetaryAmountGroup	Occurrence 0 .. unbounded Type invoice:MonetaryAmountGroup
xs:sequence	Occurrence 1 .. 1

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
MonetaryAmount	Occurrence 0 .. 1 Type <i>sharedElements:MonetaryAmount</i> General Notes MONETARY AMOUNT DETAILS
Type	Type <i>xs:string</i> Use required General Notes MONETARY AMOUNT TYPE Applicable Codes AllowanceorChargeAmount Allowance or charge amount DestinationCurrency Destination Currency
<i>xs:sequence</i>	Occurrence 1 .. 1
Amount	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes MONETARY AMOUNT
Currency	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes MONETARY AMOUNT CURRENCY
CurrencyType	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes MONETARY AMOUNT CURRENCY TYPE Applicable Codes HomeCurrency Home Currency InvoicingCurrency Invoicing Currency
Currencies	Occurrence 0 .. 1 Type <i>invoice:CurrencyGroupList</i> General Notes MONETARY AMOUNT CURRENCY DETAILS
<i>xs:sequence</i>	Occurrence 1 .. 1
CurrencyDetails	Occurrence 0 .. unbounded Type <i>invoice:CurrencyGroup</i>
<i>xs:sequence</i>	Occurrence 1 .. 1
Currency	Occurrence 0 .. 1 Type <i>sharedElements:Currency</i> General Notes CURRENCY DETAILS
<i>xs:sequence</i>	Occurrence 1 .. 1
CurrencyUsage	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes CURRENCY USAGE Applicable Codes InvoicingCurrency Invoicing Currency ReferenceCurrency Reference Currency TargetCurrency Target currency
CurrencyIdentification	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes CURRENCY IDENTIFICATION
CurrencyCode	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes CURRENCY CODE Applicable Codes HomeCurrency Home Currency Invoicing Currency Invoicing Currency Payment Currency Payment Currency PricingCurrency Pricing Currency
CurrencyRate	Occurrence 0 .. 1 Type <i>xs:string</i>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
Taxes	General Notes CURRENCY RATE Occurrence 0 .. 1 Type invoice:TaxGroupList General Notes ALLOWANCE OR CHARGE TAX DETAILS Examples <pre> <Taxes> <TaxDetails> <Tax Type="Tax" > <TaxRate>0.000</TaxRate> <TaxCode>ValueAddedTax</TaxCode> <TaxCategory>ZeroRatedGoods</TaxCategory> </Tax> <MonetaryAmounts> <MonetaryAmount Type="TaxAmount" > <Amount>0</Amount> <Currency>USD</Currency> <CurrencyType>InvoicingCurrency</CurrencyType> </MonetaryAmount> <MonetaryAmount Type="TaxAmount" > <Amount>0</Amount> <Currency>GBP</Currency> <CurrencyType>HomeCurrency</CurrencyType> </MonetaryAmount> </MonetaryAmounts> </TaxDetails> </Taxes> </pre>
xs:sequence	Occurrence 1 .. 1
TaxDetails	Occurrence 0 .. unbounded Type invoice:TaxGroup General Notes TAX DETAILS
xs:sequence	Occurrence 1 .. 1
Tax	Occurrence 0 .. 1 Type sharedElements:Tax General Notes : TAX DETAILS
Type	Type xs:string Use required General Notes TAX TYPE
xs:sequence	Occurrence 1 .. 1
TaxRate	Occurrence 0 .. 1 Type xs:string General Notes TAX RATE
TaxCode	Occurrence 0 .. 1 Type xs:string General Notes TAX CODE
TaxCategory	ValueAddedTax ValueAddedTax Occurrence 0 .. 1 Type xs:string General Notes TAX CATEGORY

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
Applicable Codes	
ExemptTax	Exempt from tax
MixedTaxRate	Mixed tax rate
StandardRate	Standard rate
VATReverseCharge	VAT Reverse Charge
ZeroRatedGoods	Zero rated goods
MonetaryAmounts	Occurrence 0 .. 1 Type <i>invoice:MonetaryAmountList</i> General Notes ALLOWANCE OR CHARGE TAX MONETARY AMOUNTS
xs:sequence	Occurrence 1 .. 1
MonetaryAmount	Occurrence 0 .. unbounded Type <i>sharedelements:MonetaryAmount</i> Type <i>xs:string</i> Use required General Notes TAX MONETARY AMOUNT TYPE
Type	
xs:sequence	Occurrence 1 .. 1
Amount	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes TAX MONETARY AMOUNT
Currency	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes TAX MONETARY AMOUNT CURRENCY
CurrencyType	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes TAX MONETARY AMOUNT CURRENCY TYPE
Applicable Codes	
TaxAmount	Tax amount
Rate	Occurrence 0 .. 1 Type <i>sharedelements:Rate</i> General Notes RATE
Type	Examples <Rate Type="SystemExchangeRate" >131.221235</Rate>
Type	Type <i>xs:string</i> Use optional General Notes RATE TYPE
Applicable Codes	
SystemExchangeRate	SystemExchangeRate
TransportStages	Occurrence 0 .. 1 Type <i>invoice:TransportStageList</i> General Notes INVOICE LINE TRANSPORT STAGES
xs:sequence	Occurrence 1 .. 1
TransportStage	Occurrence 0 .. unbounded Type <i>invoice:TransportStage</i>
xs:sequence	Occurrence 1 .. 1
Stage	Occurrence 0 .. 1 Type <i>sharedelements:Stage</i> General Notes TRANSPORT STAGE DETAILS
Examples	
<TransportStage>	

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
	Examples <pre> <Stage Type="MainCarriage" > <ModeOfTransport>Sea</ModeOfTransport> <CarrierId>12345678</CarrierId> <CarrierName>Carrier name</CarrierName> <TransportMeansName>Vessel name</TransportMeansName> </Stage> </TransportStage> </TransportStages> </pre>
Type	Type <i>xs:string</i> Use required General Notes TRANSPORT STAGE TYPE
xs:sequence	Applicable Codes MainCarriage Main Carriage
ModeOfTransport	Occurrence 1 .. 1 Occurrence 0 .. 1 Type <i>xs:string</i> General Notes MODE OF TRANSPORT
	Applicable Codes Air Air transportation Road Road transportation Sea Sea transportation
CarrierId	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes CARRIER IDENTIFICATION Air & Sea: DSV Carrier Identifier Road: Not used
CarrierName	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes CARRIER NAME Road: Not used
TransportMeansName	Occurrence 0 .. 1 Type <i>xs:string</i> General Notes TRANSPORT MEANS NAME Sea: Vessel Name Air & Road: Not used
Locations	Occurrence 0 .. 1 Type <i>invoice:LocationGroupList</i> General Notes TRANSPORT STAGE LOCATIONS
	Examples <pre> <Locations> <LocationGroup> <Location Type="Departure" > <LocationIdentification> <LocationIdentifier>USDET</LocationIdentifier> <LocationName>Detroit</LocationName> </LocationIdentification> </Location> </LocationGroup> <LocationGroup> <Location Type="Destination" > <LocationIdentification> <LocationIdentifier>GBLHF</LocationIdentifier> <LocationName>Lichfield</LocationName> </LocationIdentification> </Location> </LocationGroup> </Locations> </pre>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation								
Examples <pre> </Location> </LocationGroup> <LocationGroup> <Location Type="PlaceOfLoading" > <LocationIdentification> <LocationIdentifier>USDET</LocationIdentifier> <LocationName>Detroit</LocationName> </LocationIdentification> </Location> </LocationGroup> <LocationGroup> <Location Type="PlaceOfUnloading" > <LocationIdentification> <LocationIdentifier>GBSOU</LocationIdentifier> <LocationName>Southampton</LocationName> </LocationIdentification> </Location> </LocationGroup> </Locations> </pre>									
xs:sequence	Occurrence 1 .. 1								
LocationGroup	Occurrence 0 .. unbounded Type invoice:LocationGroup								
xs:sequence	Occurrence 1 .. 1								
Location	Occurrence 0 .. 1 Type sharedelements:Location General Notes TRANSPORT STAGE LOCATION DETAILS								
Type	Type xs:string Use required General Notes LOCATION TYPE								
Applicable Codes <table> <tr> <td>Departure</td><td>Place of Departure</td></tr> <tr> <td>Destination</td><td>Place of Destination</td></tr> <tr> <td>PlaceOfLoading</td><td>Place of Loading</td></tr> <tr> <td>PlaceOfUnloading</td><td>Place of Unloading</td></tr> </table>		Departure	Place of Departure	Destination	Place of Destination	PlaceOfLoading	Place of Loading	PlaceOfUnloading	Place of Unloading
Departure	Place of Departure								
Destination	Place of Destination								
PlaceOfLoading	Place of Loading								
PlaceOfUnloading	Place of Unloading								
xs:sequence	Occurrence 1 .. 1								
LocationIdentification	Occurrence 1 .. unbounded Type sharedelements:LocationIdentification Type xs:string General Notes LOCATION IDENTIFIER TYPE								
Type									
Applicable Codes <table> <tr> <td>GS1</td><td>GS1</td></tr> <tr> <td>IATA</td><td>IATA</td></tr> <tr> <td>UN</td><td>UN</td></tr> </table>		GS1	GS1	IATA	IATA	UN	UN		
GS1	GS1								
IATA	IATA								
UN	UN								
xs:sequence	Occurrence 1 .. 1								
LocationIdentifier	Occurrence 0 .. 1 Type xs:string General Notes LOCATION IDENTIFIER								
LocationName	Occurrence 0 .. 1 Type xs:string General Notes LOCATION NAME								
TermsOfDelivery	Occurrence 0 .. 1 Type invoice:TermsGroup General Notes INVOICE LINE TERMS OF DELIVERY								

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
Examples <TermsOfDelivery> <Terms> <TermCode>CIP</TermCode> <CodeId>IncoTerms</CodeId> </Terms> <Location Type="NamedPlace"> <LocationIdentification Type="UN"> <LocationIdentifier>DKCPH</LocationIdentifier> <LocationName>Copenhagen</LocationName> </LocationIdentification> </Location> </TermsOfDelivery>	
xs:sequence	Occurrence 1 .. 1
Terms	Occurrence 0 .. 1
xs:sequence	Type sharedelements:Terms
TermCode	Occurrence 1 .. 1
	Occurrence 0 .. 1
	Type xs:string
	General Notes TERM CODE
CodeId	Occurrence 0 .. 1
	Type xs:string
	General Notes TERM CODE IDENTIFICATION
Applicable Codes CombiTerms CombiTerms IncoTerms IncoTerms	
Location	Occurrence 0 .. unbounded
	Type sharedelements:Location
	General Notes INVOICE LINE TERMS OF DELIVERY LOCATION
Type	Type xs:string
	Use required
	General Notes LOCATION TYPE
Applicable Codes NamedPlace Named Place	
xs:sequence	Occurrence 1 .. 1
LocationIdentification	Occurrence 1 .. unbounded
	Type sharedelements:LocationIdentification
xs:sequence	Occurrence 1 .. 1
LocationName	Occurrence 0 .. 1
	Type xs:string
	General Notes LOCATION NAME
MonetaryAmounts	Occurrence 0 .. 1
	Type invoice:MonetaryAmountList
	General Notes INVOICE MONETARY AMOUNTS
Examples <MonetaryAmounts> <MonetaryAmount Type="TotalAmount" > <Amount>6790.38</Amount> <Currency>USD</Currency> <CurrencyType>InvoicingCurrency</CurrencyType> </MonetaryAmount> <MonetaryAmount Type="TotalAmount" > <Amount>5552.18</Amount> <Currency>GBP</Currency> <CurrencyType>HomeCurrency</CurrencyType> </MonetaryAmount> </MonetaryAmounts>	

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
Examples <pre> <MonetaryAmount Type="TaxableAmount" > <Amount>6790.38</Amount> <Currency>USD</Currency> <CurrencyType>InvoicingCurrency</CurrencyType> </MonetaryAmount> <MonetaryAmount Type="TaxableAmount" > <Amount>5552.18</Amount> <Currency>GBP</Currency> <CurrencyType>HomeCurrency</CurrencyType> </MonetaryAmount> <MonetaryAmount Type="TotalDutyTaxFeeAmount" > <Amount>0</Amount> <Currency>USD</Currency> <CurrencyType>InvoicingCurrency</CurrencyType> </MonetaryAmount> <MonetaryAmount Type="TotalDutyTaxFeeAmount" > <Amount>0</Amount> <Currency>GBP</Currency> <CurrencyType>HomeCurrency</CurrencyType> </MonetaryAmount> </MonetaryAmounts> </pre>	
xs:sequence	Occurrence 1 .. 1
MonetaryAmount	Occurrence 0 .. unbounded
Type	sharedElements:MonetaryAmount
Type	xs:string
Use	required
General Notes	MONETARY AMOUNT TYPE
Applicable Codes	
TaxableAmount	Taxable amount
TotalAmount	Total amount
TotalDutyTaxFeeAmount	Message total duty/tax/fee amount
xs:sequence	Occurrence 1 .. 1
Amount	Occurrence 0 .. 1
Type	xs:string
General Notes	MONETARY AMOUNT
Currency	Occurrence 0 .. 1
Type	xs:string
General Notes	MONETARY AMOUNT CURRENCY
CurrencyType	Occurrence 0 .. 1
Type	xs:string
General Notes	MONETARY AMOUNT CURRENCY TYPE
Applicable Codes	
HomeCurrency	Home Currency
InvoicingCurrency	Invoicing Currency
xs:sequence	Occurrence 0 .. 1
Taxes	Type invoice:TaxGroupList
Type	General Notes INVOICE TAX DETAILS
xs:sequence	Occurrence 1 .. 1
TaxDetails	Occurrence 0 .. unbounded
Type	invoice:TaxGroup
xs:sequence	Occurrence 1 .. 1
Tax	Occurrence 0 .. 1
Type	sharedElements:Tax
General Notes	INVOICE TAX DETAIL

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute

Annotation

Examples

```

<Taxes>
  <TaxDetails>
    <Tax Type="Tax" >
      <TaxRate>25.0000</TaxRate>
      <TaxCode>ValueAddedTax</TaxCode>
      <TaxCategory>StandardRate</TaxCategory>
    </Tax>
    <MonetaryAmounts>
      <MonetaryAmount Type="TotalDutyTaxFeeAmount" >
        <Amount>668.75</Amount>
        <Currency>EUR</Currency>
        <CurrencyType>InvoicingCurrency</CurrencyType>
      </MonetaryAmount>
      <MonetaryAmount Type="TaxableAmount" >
        <Amount>2675</Amount>
        <Currency>EUR</Currency>
        <CurrencyType>InvoicingCurrency</CurrencyType>
      </MonetaryAmount>
    </MonetaryAmounts>
  </TaxDetails>
  <TaxDetails>
    <Tax Type="TaxRelatedInformation" >
      <TaxRate>25.0000</TaxRate>
      <TaxCode>ValueAddedTax</TaxCode>
      <TaxCategory>StandardRate</TaxCategory>
    </Tax>
    <MonetaryAmounts>
      <MonetaryAmount Type="TotalDutyTaxFeeAmount" >
        <Amount>6716.855</Amount>
        <Currency>SEK</Currency>
        <CurrencyType>HomeCurrency</CurrencyType>
      </MonetaryAmount>
      <MonetaryAmount Type="TaxableAmount" >
        <Amount>26114.127</Amount>
        <Currency>SEK</Currency>
        <CurrencyType>HomeCurrency</CurrencyType>
      </MonetaryAmount>
    </MonetaryAmounts>
  </TaxDetails>
</Taxes>

```

Type

Type *xs:string*
 Use required
 General Notes TAX TYPE

Applicable Codes

Tax	Tax
TaxRelatedInformation	TaxRelatedInformation

xs:sequence

TaxRate

Occurrence 1 .. 1
 Occurrence 0 .. 1
 Type *xs:string*
 General Notes TAX RATE

TaxCode

Occurrence 0 .. 1
 Type *xs:string*
 General Notes TAX CODE

Applicable Codes

ValueAddedTax	ValueAddedTax
---------------	---------------

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
TaxCategory	<p>Occurrence 0 .. 1 Type <i>xs:string</i> General Notes TAX CATEGORY</p> <p>Applicable Codes</p> <p>ExemptTax Exempt tax MixedTaxRate Mixed tax rate StandardRate Standard rate VATReverseCharge VAT reverse charge ZeroRatedGoods Zero rated goods</p>
MonetaryAmounts	<p>Occurrence 0 .. 1 Type <i>invoice:MonetaryAmountList</i> General Notes INVOICE TAX MONETARY AMOUNTS</p> <p>Examples</p> <pre> <MonetaryAmounts> <MonetaryAmount Type="TotalDutyTaxFeeAmount" > <Amount>0</Amount> <Currency>USD</Currency> <CurrencyType>InvoicingCurrency</CurrencyType> </MonetaryAmount> <MonetaryAmount Type="TotalDutyTaxFeeAmount" > <Amount>0</Amount> <Currency>GBP</Currency> <CurrencyType>HomeCurrency</CurrencyType> </MonetaryAmount> <MonetaryAmount Type="TaxableAmount" > <Amount>6790.38</Amount> <Currency>USD</Currency> <CurrencyType>InvoicingCurrency</CurrencyType> </MonetaryAmount> <MonetaryAmount Type="TaxableAmount" > <Amount>5552.18</Amount> <Currency>GBP</Currency> <CurrencyType>HomeCurrency</CurrencyType> </MonetaryAmount> </MonetaryAmounts> </pre>
<i>xs:sequence</i>	Occurrence 1 .. 1
MonetaryAmount	<p>Occurrence 0 .. unbounded Type <i>sharedelements:MonetaryAmount</i> Type <i>xs:string</i> Use required General Notes MONETARY AMOUNT TYPE</p> <p>Applicable Codes</p> <p>TaxableAmount Taxable Amount TotalDutyTaxFeeAmount Total Duty Tax Fee Amount</p>
<i>xs:sequence</i>	Occurrence 1 .. 1
Amount	<p>Occurrence 0 .. 1 Type <i>xs:string</i> General Notes MONETARY AMOUNT</p>
Currency	<p>Occurrence 0 .. 1 Type <i>xs:string</i> General Notes MONETARY AMOUNT CURRENCY</p>
CurrencyType	<p>Occurrence 0 .. 1 Type <i>xs:string</i> General Notes MONETARY AMOUNT CURRENCY TYPE</p>

Bold = Element, Italic = Attribute, Grey = Group



Element/Attribute	Annotation
Applicable Codes	
HomeCurrency	Home Currency
InvoicingCurrency	Invoicing Currency